

HM 161.91

Digital level gauge



The illustration shows a similar water level including digital display mounted on an instrument carrier.

Description

accessory for measuring water levels

It is important to know the discharge depth for many experiments in open channel flow. The discharge depth can be measured using the level gauge HM 161.91.

The core element of HM 161.91 is a probe tip or a hook. The instrument travels vertically. The discharge depth is directly read on a digital display. The probe tip is made in way enabling to easily observe when the tip touches the water surface.

Alternatively to the probe tip, a hook can be used. To measure the discharge depth, the tip of the hook breaks through the water surface from below.

HM 161.91 is mounted on the moveable instrument carrier HM 161.59 so it can be used along the length and width of the experimental section.

Specification

- [1] device for measuring discharge depths in the experimental flume HM 161
- [2] used together with HM 161.59
- [3] measurement either with probe tip or hook
- [4] vertically travelling probe tip or hook
- [5] digital display to indicate the discharge depth
- [6] use of corrosion resistant materials

Technical data

Measuring range: 0...1000mm

■ graduation: 0,01mm

Max. travel: 800mm

LxWxH: 95x60x1180mm Weight: approx. 4kg

Scope of delivery

- 1 level gauge
- 1 set of accessories
- 1 manual



HM 161.91

Digital level gauge

Required accessories

HM 161 Experimental flume 600x800mm

HM 161.59 Instrument carrier