

HM 163.46

Set of piers, seven profiles



Learning objectives/experiments

- subcritical discharge with little or considerable reduction of cross-section
- supercritical discharge with little or considerable reduction of cross-section
- effect of the pier profile
- backwater upstream of piers
- flow transition at the pier
- effect of angle of attack

Specification

- [1] piers for the experimental flume HM 163
- [2] little or considerable reduction of cross-section caused by piers
- [3] pier profiles: rectangular, circular, square, rounded on one end, rounded on both ends, tapering profile on one end and tapering profile on both ends
- [4] pier holder with clamping device for the mounting of piers into the experimental flume: up to three piers mounted at the same time on nine different positions
- [5] pier holder with angle scale to indicate the angle of attack

Technical data

Piers made of PVC

Angle scale

- $\pm 90^\circ$
- graduation: 15°

LxWxH: 430x110x770mm (total)

Weight: approx. 32kg

Scope of delivery

- 1 set of piers with different profiles
- 1 holder with clamping device
- 1 set of accessories
- 1 manual

Description

■ lateral reduction of cross-section in the flume

Obstacles in flumes reduce the flow cross-section. This may lead to backwaters upstream of the obstacles.

HM 163.46 contains several piers with different profiles typical for bridge piers. The discharge behaviour with little reduction of cross-section is studied with a single pier. Up to three piers mounted at the same time cause a considerable reduction of cross-section.

The effect of the angle of attack can be studied by turning the mounted pier.

A clamping device fixes the pier(s) in the experimental flume. An angle scale indicates the angle between pier nose and flow.

HM 163.46

Set of piers, seven profiles

Required accessories

HM 163 Experimental flume 409x500mm